



CHECK-LIST

RIBBON SWITCHES

Mail to info@aet.fr or fax + 33(0)559 064 463

Company : _____ City : _____


Name : _____ Position : _____

E-mail : _____ Telephone : _____

YOUR DRAFT (description of your needs)

REFERENCE						
QUANTITY						
LENGTH						
QUANTITY OF LEADS ¹ SL 1 lead/FS 2 leads/SLR 1 lead	1	2	1	2	1	2
WIRING CONFIGURATION	FS (Safety Function - fail-safe 4 wires with PRSU4 control unit) SLR (Safety Function - Single lead with resistor - when used with PSSR2 6K8 or 8K2) SL (Control Function - single lead 2 wires)					
WIRING LENGTH (standard 450 mm) ²						
2° WIRING LENGTH for FS lead-2 (standard 450 mm) ²						
COLOUR ³						

- ¹ Control application : 1 live end
 Safety application : 1 live end with PSSR2 control unit and resistor
 Safety application : 2 live ends with PRSU4 control unit



- ² For other length than 450 mm, please add a surcharge
- ³ Colour choices depending on the reference

NO : Normally Open contact (when the ribbon switches is actuated, the contact will close)

Your reference : XXXX|XXXX|XX|XXXX|XXXX|XX

Ribbon switches ref / length / quantity of live end(s) / wiring length / 2° wiring length / colour

Reference	Colour	Reference	Colour
121BP	Green, black or white	TS3	Yellow, red or black
CSW	Blue	131A	Grey
141BPH	White or red	180	Red
101B	Yellow or black	151BBW	White

